

IN THE CLAIMS:

Please amend Claims 1 and 5-7 to read as follows.

The following is a complete listing of the claims in this application, reflects all changes currently being made to the claims, and replaces all earlier versions and all earlier listings of the claims:

ST
Sub
C1

1. (Currently Amended) A liquid discharge apparatus comprising:
a liquid discharge head comprising a discharge port for discharging liquid;
a liquid flow path communicating with said discharge port having a bubble generating region for generating a bubble;
a discharge energy generating element for generating thermal energy for generating the bubble in the liquid inside said bubble generating region;
and a liquid discharge head movable member facing said discharge energy generating element spaced apart from said discharge energy generating element ~~having a movable member in which~~, an end portion of said movable member situated at an upstream side in the flow direction of the liquid inside said liquid flow path is fixed and a downstream end ~~thereof~~ of said movable member is a free end;
~~in which ink is discharged from said liquid discharge head and a recording is performed by adhering said liquid on a medium to be recorded;~~
~~wherein said liquid discharge apparatus comprises:~~
means for detecting an ink supply state inside said liquid flow path; and
means for controlling or stopping the driving to said discharge energy generating element ~~when a judgment is made that the ink is~~ partially present in said flow path and the ink is not normally supplied ~~based on the detection result of the ink supply state inside said liquid flow path.~~

B1
Cust
Sub
C1
Cust

2. (Previously Amended) The liquid discharge apparatus according to Claim 1, wherein said means for detecting said ink supply state is a temperature detection means for detecting a temperature rise per unit hour inside the liquid flow path.

3. (Previously Amended) The liquid discharge apparatus according to Claim 1, further comprising a driving signal supply means for supplying a driving signal for allowing the liquid to eject from said liquid discharge head.

4. (Previously Amended) The liquid discharge apparatus according to Claim 1, further comprising a conveyance means for conveying the medium to be recorded which receives the liquid discharged from said liquid discharge head.

5. (Currently Amended) A valve protection method of a liquid discharge head having a heat generating element inside a liquid flow path communicating with a discharge port and a movable plate for directing a bubble growing by a film boiling on said heat generating element to a side of said discharge port,

wherein an ink supply state inside said liquid flow path is detected and the driving to said heat generating element is controlled or stopped when a judgment is made that an ink is partially present in said flow path and the ink is not normally supplied based on a detection result of said ink supply state.

6. (Currently Amended) A valve protection method of the liquid discharge head having a heat generating element inside the liquid flow path communicating with the discharge port and a movable plate for directing a bubble growing by a film boiling on said heat generating element to the side of said discharge port,

1312
C1
Ant

wherein the temperature rise inside said liquid flow path is detected and, when said temperature rise is more than a predetermined threshold value, a judgment is made that an ink is partially present in said flow path and the ink is not in a state of being normally supplied and the driving to said heat generating element is controlled or stopped.

7. (Currently Amended) A maintenance system of a movable member for a liquid discharge system, comprising:

a discharge port for discharging a liquid;

a liquid flow path communicating with said discharge port having a bubble generating region for generating a bubble;

a discharge energy generating element for generating thermal energy for generating the bubble in the liquid inside said bubble generating region; and

~~a liquid discharge head~~ a movable member facing said discharge energy generating element spaced apart from said discharge energy generating element ~~having a movable member in which,~~ an end portion situated at an upstream side in the flow direction of the liquid inside said liquid flow path is fixed and a down stream end ~~thereof~~ of said movable member is a free end, ~~in which by using;~~ and

a liquid supply ~~portion~~ member for supplying the liquid to ~~said a liquid discharge head,~~ the liquid is discharged;

wherein said maintenance system of said movable member for the liquid discharge system; comprises means for prohibiting or controlling the displacement of said movable member based on an ink being partially present in said flow path and a liquid supply failure condition in either of a liquid residual state inside said liquid discharge head or liquid supply state to said liquid discharge head from said liquid supply portion.